



- Electrical Test:
1. 100%Test(Open ,short ,miss wire)
  2. Contact Resistance: 1 ohm Max
  3. Insulation Resistance: 10M ohm Min
  4. Hi-Pot: 100V DC/10ms

Mold comparison table:

Inner Molding:DCN288-D-4-1-CE  
 Inner Molding:DCN697-D-4-1-CE  
 Inner Molding:SRN269-D-2-01-CE  
 Outer Molding:SRW269-D-2-01-CE

8	DC3.5, MINI DIN 4P, TV9.5 share housing Gold plated housing (24K real gold) Net tail inner OD:7.3MM no printing	3	pcs
7	1.5 Black heat shrink tube thin wall	0.014	m
6	45P black PVC material is environmentally friendly	5	9
5	Transparent PE material environmental protection low density	6	9
4	Cable clip OD:5.5MM (YB07080703)	3	pcs
3	DC3.5 FEMALE CONNECTOR Solid gold plated body (24K real gold) for 7.0MM wire diameter	2	pcs
2	DC3.5 MALE CONNECTOR Solid gold plated body (24K real gold) for 7.0MM wire diameter	1	pcs
1	NO UL 26AWG(7/0.16TC)*2C(RED, BLACK)+S(30/0.1TC) OD:5.0MM BLACK NYLON BRAIDING	0.085+0.1*2	m
NO	DESCRIPTION	Q'TY	UNIT

TOLERANCE INCHES M/M		TITLE:	
X	.015	ROLINE GOLD 3.5mm Adaptor cable (1x M, 2x F), 0.15m	
.XX	.010	P/N :	
.XXX	.005	11.09.4213	
DRAWN BY		SCALE NONE	
CHECK BY		UNIT MM	
APPD BY		DATE 2024.12.17	
		DRAWING NO.: CA1790136	
		REV. AO 1/2	

