



Pin Assignment

| | |
|----|--------|
| P1 | P2 |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| | GROUND |

Electrical Test:

1. 100%Test(Open ,short ,miss wire)
2. Contact Resistance: 1 ohm (Max)
3. Insulation Resistance: 10M ohm (Min)
4. Hi-Pot: 300V DC/10ms

Mold number

| | | |
|---------|--------------|------------------|
| DC3.5 M | Mold number: | DCN279-D-4-02-CE |
| | | DCW279-D-4-02-CE |

| | | | |
|----|---|-----|------|
| 3 | PVC~45P~Black | 12 | 9 |
| 2 | DC3.5 M~OD:6.0MM~Orichalcum Nickel plating ~Black | 2 | pcs |
| 1 | NO-UL~28AWG*2C (Red Black) +S~OD:2.8±0.1MM | 0.2 | m |
| NO | ITEM | QTY | UNIT |

| | | | |
|----------|-----------|------------------------|------------|
| | TOLERANCE | SECOMP | |
| | INCHES | | M/M |
| | .X | | .015 |
| | .XX | .010 | .10 |
| | .XXX | .005 | .05 |
| DRAWN BY | | P/N : | 11.09.4500 |
| CHECK BY | | SCALE | NONE |
| APPD BY | | UNIT | MM |
| | | DATE | 2013.03.16 |
| | | DRAWING NO.: CA1790103 | |
| | | REV. AO 1/2 | |

TITLE: ROLINE 3.5mm Cable, M/M, 0.2m