



- Electrical Test:
1. 100%Test(Open ,short ,miss wire)
 2. Contact Resistance: 2 ohm max.
 3. Insulation Resistance: 5M ohm min.
 4. Hi-pot:100V DC/10ms

Mold number:

DC	Mold number: DCW279-D-4-01-CE
	DCN279-D-4-02-CE

3	45P~Black~PVC	10	g
2	DC3.5 M OD:6.0MM Shell Nickel plating	2	pcs
1	NO-UL~28AWG*2C (red black) +S~OD:2.8±0.1MM	1.0	m
NO	CELINK P/N	QTY	UNIT
	DESCRIPTION		

<table border="1"> <tr> <th>⌀</th> <th>TOLERANCE</th> </tr> <tr> <td>.X</td> <td>.015 .30</td> </tr> <tr> <td>.XX</td> <td>.010 .10</td> </tr> <tr> <td>.XXX</td> <td>.005 .05</td> </tr> </table>	⌀	TOLERANCE	.X	.015 .30	.XX	.010 .10	.XXX	.005 .05	SECOMP TITLE: ROLINE 3.5mm Cable, M/M, 1m
⌀	TOLERANCE								
.X	.015 .30								
.XX	.010 .10								
.XXX	.005 .05								
DRAWN BY	P/N: 11.09.4501								
CHECK BY	SCALE NONE								
APPD BY	UNIT MM								
	DATE 2013.03.16								
	DRAWING NO: CA1790100								
	REV A0								
	1/2								