


PIN OUT



ITEM NO.	LENGTH
11. 99. 8909B	800 ± 20mm
11. 99. 8919B	1800 ± 30mm
11. 99. 8931B	3000 ± 50mm
11. 99. 8944B	4500 ± 100mm

NOTE:

- Electrical test:
  - 100% open short & miss wire test;
  - Insulation resistance:DC 300V 10M Ω;
  - Contact resistance:3 Ω Max;
  - Dielectric strength:100V AC/Minute, 1mA.
- RoHS 2.0 & REACH compliant
- PRINTING:USB 2.0 CABLE, 28AWG×1P+28AWG×2C

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK
③	OUTER MOLD	Shore 88A PVC(UL94V-2) Color: White	2	
②	USB A TYPE	USB A /M Type, The Pin Gold Plating 3U", the shell for Nickel Plating	2	
①	CABLE	USB 2.0 (28AWG BC*1P)+(28AWG BC*2C)+AB B(AL-MG) JACKET:PVC/WHITE OD: 3.8±0.2mm	1	

DESC.	VALUE USB 2.0 Cable Type A, M/F, white
-------	--

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		NEW	2018-12-05	A

