



Datenblatt - Fiche technique - Data sheet

12.03.3210



ROLINE Typ C - HDMI Adapter, ST/BU

ROLINE Adaptateur Type C - HDMI, M/F

ROLINE Type C - HDMI Adapter, M/F

USB 3.1 Type-C™ to HDMI A

Socket Converter

User Manual



Contents

| | |
|------------------------------|---|
| 1.0 INTRODUCTION..... | 1 |
| 2.0 FEATURES | 1 |
| 3.0 SPECIFICATIONS | 1 |
| 4.0 PACKAGE CONTENTS..... | 2 |
| 5.0 OPERATION | 2 |
| 6.0 CONNECTION DIAGRAM | 2 |

USB 3.1 Type-C™ to HDMI Socket converter

DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

1.0 INTRODUCTION

This is a USB 3.1 Type C™ to HDMI A Socket, designed for connecting HDTV & Monitor to host computer, the host computer can easily connect to the HDTV. Connecting the TV set with a HDMI cable which is contacted with the HDMI socket of this converter It can work on Mac book or Google new Chromebook Pixel or Asus Zen AiO and other USB 3.1 Type C™ supported devices.

2.0 FEATURES

- Support USB 3.1Type C™ Video output 4K*2K@30hz resolution
- Support USB 3.1Type C™ Video output 4K*2K@60hz resolution
- NO driver needed
- ABS Housing Provide white, black two colors
- Aluminium Housing Provide gold, silver, grey space, three colors
- Slim Type ABS Housing Provide white, black two colors
- With 10cm Cable
- USB 3.1Type C™ interfaces support plug and play, hot swap
- Easy to carry and use

3.0 SPECIFICATIONS

| | |
|-----------------------------------|-------------------------|
| Item No.: | |
| ABS Housing HDMI1.4b 4K*2K@30hz | 716092 716092S |
| ABS Slim Type HDMI 2.0 4K*2K@60hz | 716145 716145S |
| Aluminium Housing 1.4b 4K*2K@30hz | 716092V 716092D 719092X |
| Aluminium Housing 2.0 4K*2K@60hz | 716147 716147D 716147X |
| Size(L*W*H) | |
| ABS Housing | 200*45*15.2mm |
| ABS Slim Type housing | 200*25*11.5mm |
| Aluminium Housing | 200*38*13mm |
| Input/Output Connector | |
| Input port | USB 3.1Type C™ Male*1 |
| Output port | HDMI A Socket |
| | |
| | |

| | |
|-----------------------------|---------------------------------|
| Environmental | |
| Operating Temperature | 0°C ~ 45°C |
| Operating Humidity | 10% ~ 85 % RH (no condensation) |
| Storage Temperature | -20°C ~ 70°C |
| Storage Humidity | 5% ~ 90 % RH (no condensation) |
| System requirements | Windows, MAC OSX, Google Chrome |
| Regulatory Approvals | |
| | FCC CE Certification |
| | RoHS 2.0 & REACH Compliant |
| Accessories Adapter | |
| User Manual | English Version |

4.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

5.0 OPERATION

- 1) Connect the HDMI Socket to HDTV & Monitor
- 2) Connect the USB 3.1 Type C™ male port of this product to computer

6.0 CONNECTION DIAGRAM

