



Datenblatt - Fiche technique - Data sheet

**12.99.3142**



VALUE Mini DisplayPort-HDMI Adapter, v1.2, Mini DP ST - HDMI BU

VALUE Adaptateur Mini DisplayPort-HDMI, v1.2, MiniDP M - HDMI F

VALUE Cableadapter, v1.2, MiniDP M - HDMI F

RoHS Compliant

DATE  
2014-02-25

170±10mm

HDMI Female

P1

MINI DISPLAYPORT Male

P2

**PCBA**

SHELL	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	GROUND	WHITE	BROWN	GROUND	WHITE	GREEN	GROUND	WHITE	RED	BLACK	ORANGE	RED	WHITE	GROUND	WHITE	BLUE	GROUND	WHITE	YELLOW	YELLOW

**Mini DP**

SHELL	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	GROUND	WHITE	BROWN	GROUND	WHITE	GREEN	GROUND	WHITE	RED	BLACK	ORANGE	RED	WHITE	GROUND	WHITE	BLUE	GROUND	WHITE	YELLOW	YELLOW

Testing Requirement:  
Monitor Resolution: 3840x2160p

NO	Material	P/N	Description	Unit
6	SR	PVC-0001	60P Black PVC	0.80g
5	InnerMold	PE-0001	Low Density PE	1.80g
4	Front Case	SL-BK0065	HDMI (F) Front Cover Black	1Pcs
3	Outside Case	SL-BK0035	HDMI (F) Front Outside Case Black	1Pcs
2	Conn.	XY-C213-111-N	DP TO HDMI A/F (Black, IC: PS8402) PCBA, Nickel Connector	1Pcs
1	Cable	CB-BK-746-280	Mini DP (Assy) to Mini DP (Assy) Cable (Nickel) UL20276(32AWG*1P+D+AL/MY)*5C+32AWG*5C+MY/AL+BRAID(ALUM), JACKET PVC BLACK. OD=5.5±0.20mm	0.5Pcs

(DWG NO)	(REV)	(PAGE)	(DESIGN)	(CHECKED)	(APPROVED)	(UNIT) MM	(SCALE)
	A0	1/1					

DIMENSIONS ARE IN MILLIMETERS TOLERANCES:  
 LINEAR: X ±1.0, X.X ±0.05, X.XX ±0.025, X.XXX ±0.015  
 ANGULAR: ±0.5

**rotronic**

Model No. **12.99.3142**  
 VALUE Cable Adapter, Mini DP M to HDMI F, 1.2v  
 black