




USB-C 3.1 to 2.5GBASE-T Ethernet Adapter

TUC-ET2G (v1.0R)


- IEEE 802.3bz 2.5GBASE-T compliant
- USB-C 3.1 connection interface
- 2.5GBASE-T supports up to 2.5Gbps connection speeds
- Compatible with existing Cat5e or better cabling
- Supports 802.1p (CoS) and 802.1Q (VLAN)
- Compact design

TRENDnet's USB-C 3.1 to 2.5GBASE-T Ethernet Adapter, model TUC-ET2G, is equipped with a 2.5GBASE-T RJ-45 port that provides higher gigabit speeds capable of up to 2.5Gbps over existing Cat5e or better cabling. This USB-C 2.5G Ethernet adapter features a USB-C 3.1 interface that easily connects a USB-C enabled notebook to a high-speed 2.5GBASE-T network.




USB-C 3.1

Use the USB-C 2.5G Ethernet adapter to easily connect a USB-C 3.1 enabled notebook.



Integrated Cable


Integrated 12.6cm (4.9 in.) USB-C cable accommodates most installations.



2.5GBASE-T Port

Equipped with a 2.5GBASE-T RJ-45 port that provides gigabit speeds of up to 2.5Gbps over existing Cat5e or better cabling.

NETWORKING SOLUTION



FEATURES



USB-C 3.1

Use the USB-C 2.5G ethernet adapter to easily connect to a 2.5GBASE-T network from a USB-C 3.1 enabled notebook



2.5GBASE-T Port

Equipped with a 2.5GBASE-T RJ-45 port that provides gigabit speeds of up to 2.5Gbps over existing Cat5e or better cabling



Integrated Cable

Integrated 12.6cm (4.9 in.) USB-C cable



USB Powered

USB-C 2.5G Ethernet adapter is powered via the USB port

SPECIFICATIONS

Standards

- IEEE 802.1p
- IEEE 802.1Q
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3ab
- IEEE 802.3az
- IEEE 802.3bz
- USB-C 3.1

Interface

- 1 x 2.5GBASE-T port (2.5Gbps/1Gbps/100Mbps)
- 1 x USB-C 3.1 connector

Maximum Data Rate

- Up to 2.5Gbps (2.5GBASE-T port)

Special Features

- Energy saving technology
- Wake on LAN (suspend mode)

Compatibility

- Windows® 10, 8.1, 7
- MacOS® 10.13.5, 10.13.6

Operating Temperature

- 0° – 40° C (32° – 104° F)

Operating Humidity

- Max. 90% non-condensing

Power

- USB powered

Dimensions

- 84 x 32 x 13mm (3.3 x 1.25 x 0.51 in.)
- 12.6cm (4.9 in.) cable length

Weight

- 30g (1.05 oz.)

Certifications

- CE
- FCC

Warranty

- 2 year

Package Contents

- TUC-ET2G
- CD-ROM (Drivers & User Guide)
- Quick Installation Guide