


NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel TEST:
TEST LIMIT:ISO11801 Channel Class EA
3. Working temperature:-10°C~+60°C
Storage temperature:-20°C~+75°C
4. RoHS2.0 AND REACH compliant
5. Spray WORD:CAT6A U/FTP 4x2x32AWG/7 Ultraflex LSZH-TPE ISO11801 & EN50173 & ANSI/TIA568C.2
6. Minimum of the bending radius is 15mm(Suitable for all meters)

PIN OUT



| | CN1 (568B) | | CN2 (568B) |
|--------------|------------|---|----------------|
| WHITE-ORANGE | 1 | — | 1 WHITE-ORANGE |
| ORANGE | 2 | — | 2 ORANGE |
| WHITE-GREEN | 3 | — | 3 WHITE-GREEN |
| GREEN | 6 | — | 6 GREEN |
| BLUE | 4 | — | 4 BLUE |
| WHITE-BLUE | 5 | — | 5 WHITE-BLUE |
| WHITE-BROWN | 7 | — | 7 WHITE-BROWN |
| BROWN | 8 | — | 8 BROWN |
| SHELL | | — | SHELL |

MATERIAL LIST

| NO. | PARTS NAME | SPECIFICATION STANDARD | QT' Y | REMARK |
|-----|------------|-------------------------------------------------------------------------------------------------------------|-------|--------|
| ③ | OVER MOLD | 75A PVC BLACK (PANTONE3C) | 2 | |
| ② | PLUG | RJ45 8P8C Shielded Plug, PIN GOLD PLATED 3u", THE SHELL PLATED NICKEL, COLOUR: TRANSPARENT | 2 | |
| ① | CABLE | CAT. 6A U/FTP CABLE (32AWG BC*1P+AL-FOIL)*4+DRAIN JACKET:ULTRAFLEX LSZH-TPE/BLACK (PANTONE3C), OD:3.6±0.2MM | 1 | |

| Item NO. | Length (mm) |
|------------|-------------|
| 21.44.3350 | 150±10 |
| 21.44.3351 | 300±10 |
| 21.44.3352 | 500±20 |
| 21.44.3353 | 1000±20 |
| 21.44.3354 | 1500±30 |
| 21.44.3355 | 2000±30 |
| 21.44.3356 | 3000±50 |
| 21.44.3357 | 5000±100 |

| DESC. | ROLINE GREEN Cat. 6A U/FTP Patch cord 10G Slim Type Ultraflex LSZH-TPE, black |
|-------|-------------------------------------------------------------------------------|
|-------|-------------------------------------------------------------------------------|

| | | | | |
|----|-----|-------------------------------|------------|------|
| | | NEW | 2022-07-01 | A |
| BY | CHK | REVISION RECORD MODIFICATIONS | DATE | REV. |

SECOMP