



|   |   |  |
|---|---|--|
| <b>Anschlusskabel 10A</b>   | <b>power cable 10A</b>  | <b>cable de raccordement 10A</b>   |
| <u>Leitungs- und Steckertyp:</u><br>H05VV-F 3G1,0mm <sup>2</sup> 1,0m <ul style="list-style-type: none"> <li>Seite 1: IEC320 C14 Stecker 10A</li> <li>Seite 2: IEC320 C13 Buchse 10A</li> </ul>                                   | <u>Cable and plug type:</u><br>H05VV-F 3G1,0mm <sup>2</sup> 1,0m <ul style="list-style-type: none"> <li>Side 1: IEC 320 C14 plug 10amp</li> <li>Side 2: IEC320 C13 connector 10amp</li> </ul>   | <u>Type de connecteur et cable:</u><br>H05VV-F 3G1,0mm <sup>2</sup> 1,0m <ul style="list-style-type: none"> <li>Extrémité 1 : IEC 320 C14 connecteur 10amp</li> <li>Extrémité 2 : IEC 320 C13 connecteur 10amp</li> </ul>              |
| <u>Lieferform:</u> <ul style="list-style-type: none"> <li>Neutrale Polybeutel</li> <li>mit Schroff Art.-Nr. und Barcode 39</li> </ul>   | <u>Form of delivery:</u> <ul style="list-style-type: none"> <li>Neutral polybag</li> <li>With Schroff Item no. and bar code 39</li> </ul>   | <u>Conditionnement :</u> <ul style="list-style-type: none"> <li>Emballage dans un sachet de plastic</li> <li>Avec réf. Schroff et code barre 39</li> </ul>   |
| <u>Lieferumfang:</u> <ul style="list-style-type: none"> <li>1 x Anschlusskabel</li> </ul>   | <u>Extent of delivery:</u> <ul style="list-style-type: none"> <li>1 x power cable</li> </ul>  | <u>Composition :</u> <ul style="list-style-type: none"> <li>1 x cable de raccordement</li> </ul>   |
| <u>Thermische Eigenschaften</u> <ul style="list-style-type: none"> <li>Betriebs- Umgebungstemperatur 0 ... +55°C</li> <li>Lagertemperatur -20... +75°C</li> <li>Betriebs-Umgebungsfeuchte 5... 95% nicht kondensierend</li> </ul> | <u>Thermal specifications</u> <ul style="list-style-type: none"> <li>Operating temperature range 0...+55°C</li> <li>Storage temperature range -20... +75°C</li> <li>Operating humidity range 5...95% relative humidity, non-condensing</li> </ul> | <u>Spécification thermiques</u> <ul style="list-style-type: none"> <li>Temperature de fonctionnement 0°. +55°</li> <li>Temperature de stockage -20°... +75°</li> <li>Humidité en fonctionnement 5%... 95% sans condensation</li> </ul> |